




- Print speeds listed below reflect measured values based on Canon's unique measurement conditions and are for reference only.
- Actual print speeds may vary depending on printing conditions (document complexity, print frequency, temperature, humidity, printer driver settings and version, application used, system requirements, interface, type of paper used, direct print settings, etc.). Print speeds listed below do not take into account data processing time on host computer and data transfer time.
- Print speeds are calculated by rounding off the actual measurement value to the nearest integer.

	Print Speed on Photo Paper (Required time for making a print)		Direct Print Speed on Photo Paper (Required time for making a print)	
Print Pattern	Image data (1)  4"x6" borderless ISO/JIS-SCID N2		5 megapixel image test print	
Image Size	Image data(1): 4" x 6"		4" x 6"	
Measurement Method	See *1 below		PictBridge:See *2 below	
Media	Canon Photo Paper Plus Glossy PP-101		Canon Photo Paper Plus Glossy PP-101	
Settings	Page Size	4"x6"	Paper Size Setting	4"x6"
	Media Type	Photo Paper Plus Glossy	Paper Type	Photo (Photo Paper Plus Glossy)
	Print Quality	Standard (Default)	-	-
	Borderless	ON	Borderless	ON
Application	Adobe Photoshop 7.0		N/A	
PC environment	OS: Microsoft Windows XP Professional SP2 CPU: Intel Pentium4 3.0 GHz RAM: 1GB Interface: USB			
Notes	<p>*1 Print speeds on photo paper are measured based upon making a single print under the above measurement conditions, starting from the beginning of paper feed using the automatic sheet feeder to the end of paper ejection.</p> <p>*2 When printing a 5 megapixel image taken by 5 megapixel digital camera from PictBridge on default settings using select Canon photo paper without borders. Print speeds are measured based on making a single print, starting from the time when pressing the Start key to the end of paper ejection.</p>			