







- Print speeds listed below reflect measured values based on Canon's unique measurement conditions and are for reference only.
- Actual print speeds may vary depending on printing conditions (document complexity, print frequency, temperature, humidity, printer driver settings and version, application used, system requirements, interface, type of paper used, direct print settings, etc.). Print speeds listed below do not take into account data processing time on host computer and data transfer time.
- Print speeds are calculated by rounding off the actual measurement value to the nearest integer.

| | Print Speed on Photo Paper (Required time for making a print) | | Print Speed on Plain Paper (number of continuous prints) | |
|--------------------|---|--|---|--|
| Print Pattern | Image data (1)  4"x6" borderless ISO/JIS-SCID N2 | Image data (2)*3  Letter(8.5"x11") ISO/JIS-SCID N5 | Image data (3)  A4/Letter Monochrome Document Canon Standard Pattern | Image data (4)  A4/Letter Color Document Canon Standard Pattern |
| Image Size | Image data(1): 4" x 6" Image data(2): 8.5" x 11" | | | |
| Measurement Method | See *1 below | | See *2 below | |
| Media | Canon Photo Paper Plus Glossy PP-101 Canon Photo Paper Pro PR-101 *3 | | Plain Paper | |
| Settings | Page Size | 4"x6" or Letter | Page Size | A4/Letter |
| | Media Type | Photo Paper Plus Glossy | Media Type | Plain Paper |
| | | Photo Paper Pro *3 | | |
| | Print Quality | Standard (Default) | Print Quality | Custom Setting 5 |
| | Borderless | 4"x6": ON | Borderless | OFF |
| | | Letter: ON *3 | | |
| Application | Adobe Photoshop 7.0 | | Microsoft Word 2002 | |
| PC environment | OS: Microsoft Windows XP Professional SP2 CPU: Intel Pentium4 3.0 GHz RAM: 1GB Interface: USB2.0 Hi-Speed used when applicable | | | |
| Notes | <p>*1 Print speeds on photo paper are measured based upon making a print under the above measurement conditions, starting from the beginning of paper feed using the automatic sheet feeder to the end of paper ejection.</p> <p>*2 Print speeds on plain paper are measured based on making a continuous printing for more than 60 seconds under the above measurement conditions, starting from the beginning of the 1st sheet feeding from the automatic sheet feeder to the end of paper ejection of the sheet being printed 60 seconds after the start of printing.</p> <p>*3 Only for iP6600D/iP6220D/iP6210D</p> | | | |