

Canon

LASER CLASS 710



**WORKGROUP
SYSTEMS**



LASER CLASS 710 Series Specifications

Type:	Desktop Transceiver
Applicable Line:	Public Switched Telephone Network
Compatibility:	G3
Automatic Document Feeder:	Up to 70 Sheets (Letter)* Up to 30 Sheets (Legal)* Up to 30 Sheets (Ledger)*
Scanning Method:	Contact Image Sensor
Document Sizes:	Maximum: 11" x 39.4" (279mm x 1000mm) Minimum: 5.9" x 5" (148mm x 128mm) 10" (254mm)
Effective Scanning Width:	10" (254mm)
InstaScan:	Approx. 1.1 Sec./Page (Letter, Standard Mode) Approx. 35 Scans/Min. (Letter, Standard Mode)
Data Compression System:	MH, MR, MMR, JBIG ^{†††}
Modem Speed:	33.6/31.2/28.8/26.4/24/21.6/19.2/16.8/ 14.4/12/9.6/7.2/4.8/2.4 Kbps Automatic Fallback
Transmission Speed:	Approx. 3 Sec./Page** (V.34/33.6 Kbps + JBIG)
Printing Method:	Laser Dry Electrostatic Transfer
Printing Speed:	Up to 19 Pages/Min. (Letter)
Halftone:	256 Shades of Gray
TX/RX Resolution:	Horizontal Vertical
Ultra Fine Mode:	406 pels/in. x 391 lines/in. 16 pels/mm x 15.4 lines/mm
Super Fine Mode:	203 pels/in. x 391 lines/in. 8 pels/mm x 15.4 lines/mm
Fine Mode:	203 pels/in. x 196 lines/in. 8 pels/mm x 7.7 lines/mm
Standard Mode:	203 pels/in. x 98 lines/in. 8 pels/mm x 3.85 lines/mm
Effective Recording Width:	8.2" (210mm)
Recording Paper Supply:	600 Sheets: 2 x 250-Sheet, Adjustable Cassette; 100-Sheet MP Tray; Optional 500-Sheet Cassette (Letter)
Receiving Paper Tray:	Face-Down, Print-In-Order: 250 Sheets
Recording Paper Size:	Letter/Legal/A4
Enhanced Imaging Quality:	UHQ (Ultra High Quality)
Enhanced Printing Quality:	1200-dpi Smoothing for Incoming Faxes
Printing Resolution:	1200 dpi x 1200 dpi
Printer Cartridge:	FX7 Cartridge
Cartridge Yield:	Approx. 4,500 Pages ^{††}
Power Consumption:	
Standby:	Approx. 15W
Max.:	Approx. 980W
Energy Saver:	5W
Dimensions (H x W x D)	
Without Handset:	18-1/8" x 19-3/4" x 19-3/4" (459mm x 499mm x 499mm)
With Handset:	18-1/8" x 22-1/2" x 19-3/4" (459mm x 569mm x 499mm)

Weight (Excluding Handset Option):	Approx. 52 lb. 15 oz. (24kg)
Environmental Conditions	
Temperature:	50°F - 90.5°F (10°C - 32.5°C)
Humidity:	20% - 80% RH
Dialing:	Automatic Dialing One-Touch Speed-Dialing: 72 Locations Coded Speed-Dialing: 128 Locations Group-Dialing: 199 Groups Each Group Can Accommodate up to 199 Locations Maximum Dial Digits: 120 Error Re-Dialing Manual Re-Dialing Dial Search Energy Saver Key Programmable Key
Delayed Transmission:	Up to 210 Destinations and up to 70 Reservations
Memory Polling Transmission	
Polling Reception	
Multi-Polling:	Up to 210 Locations
Delayed Polling:	Up to 200 Locations Up to 5 Designated Times per Speed-Dial Up to 210 Locations (200 Pre-Programmed Speed-Dials)
Sequential Broadcast:	
Relay Broadcast:	Up to 200 Locations
Relay Boxes:	Up to 50
Delayed Relay Broadcast:	Up to 5 Designated Times per Speed-Dial
Relay Broadcast Command	
Transmission to Confidential Mail Box	
Confidential Mail Box:	Up to 50 Boxes
Memory Transmission/Reception:	(8MB) Up to 510 Pages (Standard) ⁼ One Open Slot, Optional 32MB for Total Capacity
Password and Sub-Address (ITU-T STD)	
Convenience:	Auto Receive Reduction (70% ~ 100%) Dual Access TX Reservation During RX TX Reservation During Memory TX Memory RX During Copy Memory TX During Copy Scan During Printing
Transmission Reservation:	Up to 70 Reservations
LCD (Liquid Crystal Display):	20-Digits x 2-Line
Department Access Code:	Up to 99 Codes
Local Copy Function:	Multiple Copy up to 99 Pages
Program Buttons:	Up to 72
Memory Lock Reception	
Battery Backup:	Up to 12 Hours [†]
RX Document Multiple Printout:	Up to 99 Pages
RX Page Footer:	Yes
Transfer Mode:	Yes
Soft Counter:	Yes

Report/Reference:	Activity Report (up to 40 Transactions) Non-Delivery Report Management Report List of Phone Numbers for One-Touch and Coded Speed-Dialing List of Transaction Schedule User Data List File Reference TTI (Transmitter Terminal Identification) TTI Selector: Up to 99 Identifications RTI (Remote Terminal Identification) 33.6 Kbps Dual Line 500-Sheet Cassette (Letter) Stamp Stamp Refill Telephone Handset Kit 8 Pedestal ⁼ (H x W x D): 17-3/4" x 18-7/8" x 17-1/2" (450mm x 478mm x 444mm)
Options:	Facsimile Memory: 32MB Printer Memory: 32MB, 64MB
Provided by Third-Party:	

* 15-27.5° C; 20-80% RH; 20 lb., < 120 µm
 ** Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (JBIG, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speeds or lower, depending on telephone line conditions.
 † When the system is configured with 40MB memory, battery backup is reduced to three hours maximum (see page 3).
 †† Based on 4% Original, 5% Coverage.
 ††† Actual Compression Ratio may vary with image.
 =Based on ITU-T No. 1 Chart (Standard Mode).
 = Requires 500-Sheet letter-sized cassette.

Canon
image*ANYWARE*

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. IPX/SPX is a trademark of Novell, Inc. Solaris is a trademark of Sun Microsystems, Inc. in the United States and other countries. Flash is a trademark of Macromedia, Inc. in the United States and/or other countries. CANON and LASER CLASS are registered trademarks, and the SUPER G3 logo is a trademark of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners.

Specifications and availability subject to change without notice.

©2009 Canon U.S.A., Inc. All rights reserved.